

# PRODUCT SPECIFICATION

### GENERAL

FINISH: Matt Nickel CABLE LENGTH: Not Applicable MAIN MATERIAL: Metal - Zinc **GROSS WEIGHT:** 1.2 (kg) H: 80mm W: 190mm D: 173mm **DIMENSIONS:** CLASS: CE (Class II) INSTALLATION ORIENTATION: Wall Mount - Horizontal IP RATING: IP20 Not Applicable **CUT OUT HOLE: BATHROOM ZONE:** Zone 3 **RECESS DEPTH:** 60 mm **VOLTAGE:** Mains 230V

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE: High-Power LED MACADAM ELIPSE: 3-Step MAXIMUM WATTAGE: 3W UGR: Not Applicable

MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** 25.6 (Degrees) LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: 180 (Degrees) **LUMINOUS FLUX:** 114.1 (lm) **ROTATION ADJUSTMENT ANGLE:** 90 (Degrees) **COLOUR TEMP:** AVERAGE LIFESPAN: 2700 (K) 54,000 (Hrs) CRI: 85 L70: To Be Advised

20.6 R9:

**ELECTRICAL** 

SWITCHED: SUPPLY FREQUENCY: Yes 50/60 (Hz) DIMMABLE: No DRIVER/BALLAST VOLTAGE: 100-240 (V) DIMMING METHOD: Not Applicable DRIVER AVERAGE LIFESPAN: 60,000 (Hrs) **DRIVER OUTPUT CURRENT:** 700 (mA) EFFICACY: 29.64 (lm/W) DRIVER OUTPUT VOLTAGE: DRIVER INCLUDED?

ADDITIONAL INFORMATION


Not Applicable

**BOX QUANTITY X6** 


Œ

Yes (Integral)


### TOP




## FRONT



# BACK



# SIDE



T: +44 (0) 1279 427001 F: +44 (0) 1279 427002 sales@astrolighting.com www.astrolighting.com